



MODEL# LEDG-RTSN-480D

### SPECIFICATIONS

**Input Voltage** : AC100-277V (347V/480V available)  
**Input Wattage** : 480 watts  
**Power Factor** : 0.9  
**Operating Frequency** : 50/60Hz  
**LED Count** : 560  
**Led Type** : Phillips 3030, 1.5W  
**Delivered Lumens (Lm)** : 48000-62000  
**Efficacy Lm/Watt** : 114.58333333333333  
**Color Rendering Index (CRI)** : >80  
**Color Temperature** : 4000K, 4500K, 5000K, 5700K  
**Equivalent Wattage** : 3500 watt incandescent/1000 watt CFL  
**Beam Angle Degrees** : 120  
**Beam Type** : Wide Fixed  
**Available Optics** : 120 Beam  
**Lens Cover** : None  
**Driver Type** : HLG-240H-48B\*2 ( Mean Well Driver )  
**Connection Options** : Direct Wire  
**Power Delivery Options** : External Driver to Line Voltage  
**Mounting Options** : Patented Multi-Purpose Bracket  
**Min. Ambient Temp (°F)or(°C)** : Minus 20 degrees Celsius  
**Min. Starting Temperature (°F)or(°C)** : Minus 20 degrees Celsius  
**Maximum Ambient temp (°F)or(°C)** : 45 degrees Celsius  
**Dimming Capability** : Yes  
**Min Dimming Level** : 0.1  
**L70 Life (Hours)** : 50,000  
**Warranty** : 5 Years  
**Product Length** : 14.96-17.51  
**Product Width** : 10.23  
**Product Height** : 5.11-6.29  
**IP Rating** : 40  
**Construction Material** : Aluminum  
**Dimmable** : Yes / Option  
**Certification**: UL Listed, DLC, RoHs, FCC, CE,

### HIGHBAY BRACKET



### UNIVERSAL BRACKET

