



MODEL# LEDG-CLW-7WA1

SPECIFICATIONS

Input Voltage : AC100-277V

Input Wattage : 7

Power Factor : >90

Operating Frequency : 50/60Hz

LED Count : 60

Led Type : SMD Epistar 3014

Delivered Lumens (Lm) : 590

Efficacy Lm/Watt : 106

Color Rendering Index (CRI) : >75

Color Temperature : 2700-3000K, 4000-4500K, 6000-6500K

Equivalent Wattage : 40 W Incandescent/ 13 W CFL

Beam Angle Degrees : 120 (Base rotates)

Beam Type : Direct

Available Optics : None

Lens Cover : Frosted, Clear

Driver Type : Constant current/Isolated

Net Weight : 0.1kg

Connection Options : E26, G24, GX24

Mounting Options : E26, G24

Min. Ambient Temp (°F)or(°C) : Minus 20 C

Min. Starting Temperature (°F)or(°C) : Minus 20 C

Maximum Ambient temp (°F)or(°C) : 45 Degrees Celsius

Dimming Capability : N

L70 Life (Hours) : 50000

Warranty : 3 Years

Product Length : 123/130

Product Width : 45/45

IP Rating : IP 65 (Driver)

Construction Material : Aluminum / PC

Non-Dimmable : Y

Certification: UL Listed, RoHs, FCC, CE,

Product Testing: LM-80,

