



MODEL# **LEDG-CLW-6WA1**

SPECIFICATIONS

Input Voltage : AC100-277V
Input Wattage : 6
Power Factor : >90
Operating Frequency : 50/60Hz
LED Count : 60
Led Type : SMD Epistar 3014
Delivered Lumens (Lm) : 635
Efficacy Lm/Watt : 106
Color Rendering Index (CRI) : >75
Color Temperature : 2700-3000K, 4000-4500K, 6000-6500K
Equivalent Wattage : 30 W Incandescent/ 13 W CFL
Beam Angle Degrees : 120 (Base rotates)
Beam Type : Direct
Available Optics : None
Lens Cover : Frosted, Clear
Driver Type : Constant current/Isolated
Net Weight : 0.1kg
Connection Options : E26, G24
Mounting Options : E26, G24
Min. Ambient Temp (°F)or(°C) : Minus 20 C
Min. Starting Temperature (°F)or(°C) : Minus 20 C
Maximum Ambient temp (°F)or(°C) : 45 Degrees Celsius
L70 Life (Hours) : 50000
Warranty : 3 Years
Product Length : 123/130
Product Width : 45/45
IP Rating : IP 65 (Driver)
Construction Material : Aluminum / PC
Non-Dimmable : Y
Certification: UL Listed, RoHs, FCC, CE,
Product Testing: LM-80,

