



MODEL# T8L-IDBH11-1800-4ft-XXX

SPECIFICATIONS

Input Voltage : 120-277 or Ballast Compatible (DLC TYPE AB)

Input Wattage : 15

Power Factor : 0.9

Operating Frequency : 50/60Hz

LED Count : 228

Led Type : 3014 SMD

Delivered Lumens (Lm) : 1800

Efficacy Lm/Watt : 120

Color Rendering Index (CRI) : > 85

Color Temperature : 4000

Equivalent Wattage : 32-40

Beam Angle Degrees : 240

Lens Cover : Frosted

Driver Type : INT

Net Weight : 700 grams

Connection Options : G13 Non-Rotating

Power Delivery Options : Ballast Compatible, Line Voltage

Mounting Options : G13 med b ipin

Min. Ambient Temp (°F)or(°C) : -40° F

Maximum Ambient temp (°F)or(°C) : 140 ° F

Dimming Capability : No

L70 Life (Hours) : >50,000 hours

Warranty : 5 Years

Product Length : 1200 mm

IP Rating : 54

Construction Material : Aluminum, Poly carbonite

Dimmable : No

Non-Dimmable : Yes

Certification: UL Classified, UL Listed, DLC, RoHs, FCC, CE,

Product Testing: LM-79, LM-80, IES ,

