



MODEL# T8L-IDBH11-1800-4ft-XXX

## SPECIFICATIONS

**Input Voltage** : 120-277 or Ballast Compatible ( DLC TYPE AB)

**Input Wattage** : 15

**Power Factor** : 0.9

**Operating Frequency** : 50/60Hz

**LED Count** : 228

**Led Type** : 3014 SMD

**Delivered Lumens (Lm)** : 1800

**Efficacy Lm/Watt** : 120

**Color Rendering Index (CRI)** : > 85

**Color Temperature** : 4000

**Equivalent Wattage** : 32-40

**Beam Angle Degrees** : 240

**Lens Cover** : Frosted

**Driver Type** : INT

**Net Weight** : 700 grams

**Connection Options** : G13 Non-Rotating

**Power Delivery Options** : Ballast Compatible, Line Voltage

**Mounting Options** : G13 med b ipin

**Min. Ambient Temp (°F)or(°C)** : -40° F

**Maximum Ambient temp (°F)or(°C)** : 140 ° F

**Dimming Capability** : No

**L70 Life (Hours)** : >50,000 hours

**Warranty** : 5 Years

**Product Length** : 1200 mm

**IP Rating** : 54

**Construction Material** : Aluminum, Poly carbonite

**Dimmable** : No

**Non-Dimmable** : Yes

**Certification**: UL Classified, UL Listed, DLC, RoHs, FCC, CE,

Product Testing: LM-79, LM-80, IES ,

