



MODEL# LEDG-30-CNS-IP64

## SPECIFICATIONS

**Input Voltage** : 100-277 VAC

**Input Wattage** : 30 watts

**Power Factor** : >90

**Operating Frequency** : 50/60hz

**LED Count** : 228

**Led Type** : Epistar SMD 2835

**Delivered Lumens (Lm)** : 3000-3450

**Efficacy Lm/Watt** : 100-115

**Color Rendering Index (CRI)** : >80

**Color Temperature** : 4000K, 4500K, 5000K, 5700K

**Equivalent Wattage** : 300 watt Incandescent, 100 watt CFL

**Beam Angle Degrees** : 360

**Lens Cover** : Clear

**Driver Type** : Internal Insolated

**Connection Options** : E39

**Min. Ambient Temp (°F)or(°C)** : -20 degrees C

**Min. Starting Temperature (°F)or(°C)** : -20 degrees C

**Maximum Ambient temp (°F)or(°C)** : 45 degrees C

**Dimming Capability** : N

**L70 Life (Hours)** : 50000

**Warranty** : 5 years

**Product Length** : 8.07 in.(E26), 8.85 in.(E40)

**Product Width** : 3.66 in.(E26 & E40)

**IP Rating** : 64

**Construction Material** : Aluminum and PC

**Dimmable** : N

**Certification**: UL Listed, RoHs, FCC, CE,

