



MODEL# LEDGREEN-H2UFO200W275K

## SPECIFICATIONS

**Input Voltage** : AC90-305V  
**Input Wattage** : 200 watts  
**Power Factor** : 0.95  
**Operating Frequency** : 50-60 Hz  
**LED Count** : 280  
**Led Type** : Phillips Lumileds 3030  
**Delivered Lumens (Lm)** : 30,000  
**Efficacy Lm/Watt** : 150 lm/w  
**Color Rendering Index (CRI)** : >70  
**Color Temperature** : 3000-6000  
**Equivalent Wattage** : 750 watt  
**Beam Angle Degrees** : 105  
**Lens Cover** : PC Frosted or Transparent  
**Driver Type** : Inventronics  
**Net Weight** : 8.8 kg  
**Connection Options** : 3 core 18 AWG  
**Mounting Options** : Chain, Pendant, Ceiling Mount, Suspended Mount  
**Min. Ambient Temp (°F)or(°C)** : -20 degrees C  
**Min. Starting Temperature (°F)or(°C)** : -20 degrees C  
**Maximum Ambient temp (°F)or(°C)** : 40 degrees C  
**Dimming Capability** : 20%  
**L70 Life (Hours)** : 50,000  
**Warranty** : 5 years  
**Product Length** : 400mm  
**Product Height** : 190mm  
**IP Rating** : 65  
**Construction Material** : Die-Cast Aluminum  
**Dimmable** : Yes  
**Certification**: UL Listed, PG&E Certified, DLC, RoHs, FCC, CE, C-Tick, PSE,  
Product Testing: LM-79, LM-80, IES ,

