



MODEL# LEDGREEN-H2UFO200W275K

SPECIFICATIONS

Input Voltage : AC180-528V
Input Wattage : 200 watts
Power Factor : 0.95
Operating Frequency : 50-60 Hz
LED Count : 280
Led Type : Phillips Lumileds 3030
Delivered Lumens (Lm) : 30,000
Efficacy Lm/Watt : 150 lm/w
Color Rendering Index (CRI) : >70
Color Temperature : 3000-6000
Equivalent Wattage : 750 watt
Beam Angle Degrees : 105
Lens Cover : PC Frosted or Transparent
Driver Type : Meanwell
Net Weight : 8.8 kg
Connection Options : 3 core 18 AWG
Mounting Options : Chain, Pendant, Ceiling Mount, Suspended Mount
Min. Ambient Temp (°F)or(°C) : -20 degrees C
Min. Starting Temperature (°F)or(°C) : -20 degrees C
Maximum Ambient temp (°F)or(°C) : 40 degrees C
Dimming Capability : 20%
L70 Life (Hours) : 50,000
Warranty : 5 years
Product Length : 400mm
Product Height : 190mm
IP Rating : 65
Construction Material : Die-Cast Aluminum
Dimmable : Yes
Certification: UL Listed, PG&E Certified, DLC, RoHs, FCC, CE, C-Tick, PSE,
Product Testing: LM-79, LM-80, IES ,

