



MODEL# LEDGREEN-H2UFO250W275K

SPECIFICATIONS

Input Voltage : AC180-528V

Input Wattage : 250 watts

Power Factor : 0.95

Operating Frequency : 50-60 Hz

LED Count : 280

Led Type : Phillips Lumileds 3030

Delivered Lumens (Lm) : 37,500

Efficacy Lm/Watt : 150 lm/w

Color Rendering Index (CRI) : >70

Color Temperature : 3000-6000

Equivalent Wattage : 900 watt

Beam Angle Degrees : 105

Lens Cover : PC Frosted or Transparent

Driver Type : Meanwell

Net Weight : 8.8 kg

Connection Options : 3 core 18 AWG

Mounting Options : Chain, Pendant, Ceiling Mount, Suspended Mount

Min. Ambient Temp (°F)or(°C) : -20 degrees C

Min. Starting Temperature (°F)or(°C) : -20 degrees C

Maximum Ambient temp (°F)or(°C) : 40 degrees C

Dimming Capability : 20%

L70 Life (Hours) : 50,000

Warranty : 5 years

Product Length : 400mm

Product Height : 190mm

IP Rating : 65

Construction Material : Die-Cast Aluminum

Dimmable : Yes

Certification: UL Listed, PG&E Certified, DLC, RoHs, FCC, CE, C-Tick, PSE,

Product Testing: LM-79, LM-80, IES ,

