



MODEL# LEDG-80R SMD 90-300

## SPECIFICATIONS

**Input Voltage** : 100-277V  
**Input Wattage** : 83 watts  
**Power Factor** : .90  
**Operating Frequency** : 50/60Hz  
**LED Count** : 560  
**Led Type** : Epistar SMD 2835  
**Delivered Lumens (Lm)** : 10,400  
**Efficacy Lm/Watt** : 130 lm/w  
**Color Rendering Index (CRI)** : >80  
**Color Temperature** : 3000, 4000, 6000K  
**Equivalent Wattage** : 250 watt  
**Beam Angle Degrees** : 360  
**Driver Type** : Internal Isolated  
**Net Weight** : 0.67kg  
**Connection Options** : E39  
**Mounting Options** : Screw in Base  
**Min. Ambient Temp (°F)or(°C)** : -20 degrees C  
**Min. Starting Temperature (°F)or(°C)** :  
**Maximum Ambient temp (°F)or(°C)** : 45 degrees C  
**Dimming Capability** : Non-Dimmable  
**L70 Life (Hours)** : 50,000  
**Warranty** : 5 Years  
**Product Length** : 296mm  
**Product Width** : 118mm  
**IP Rating** : 40  
**Construction Material** : Aluminum / PC  
**Non-Dimmable** : Y  
**Certification**: UL Listed, RoHs, FCC, CE, PSE,  
Product Testing: LM-79, LM-80, IES ,

