



MODEL# LEDG-15-CNS-IP64

## SPECIFICATIONS

**Input Voltage** : 100-277 VAC

**Input Wattage** : 15 watts

**Power Factor** : >90

**Operating Frequency** : 50/60hz

**LED Count** : 120

**Led Type** : Epistar SMD 2835

**Delivered Lumens (Lm)** : 1500-1720

**Efficacy Lm/Watt** : 100-115

**Color Rendering Index (CRI)** : >80

**Color Temperature** : 2700-6500K

**Equivalent Wattage** : 30 watt CFL, 50 watt HID

**Beam Angle Degrees** : 360

**Lens Cover** : Clear

**Driver Type** : Internal Insolated

**Connection Options** : E26

**Min. Ambient Temp (°F)or(°C)** : -20 degrees C

**Min. Starting Temperature (°F)or(°C)** : -20 degrees C

**Maximum Ambient temp (°F)or(°C)** : 45 degrees C

**Dimming Capability** : N

**L70 Life (Hours)** : 50000

**Warranty** : 5 years

**Product Length** : 6.10 in.(G24), 6.29 in.(E26)

**Product Width** : 2.16 in.(G24), 2.75 in.(E26)

**IP Rating** : 64

**Construction Material** : PC and Aluminum

**Dimmable** : N

**Certification**: UL Listed, RoHs, FCC, CE,

