



MODEL# LEDG-RTSN-35-4500K

SPECIFICATIONS

Input Voltage : AC100-277V (347V/480V available)

Input Wattage : 35 watts

Power Factor : 0.9

Operating Frequency : 50/60Hz

LED Count : 14

Led Type : High Power CREE XTE,1-5W

Delivered Lumens (Lm) : 3661

Efficacy Lm/Watt : 104.6

Color Rendering Index (CRI) : >80

Color Temperature : 4500

Equivalent Wattage : 200

Beam Angle Degrees : 120 Degrees

Beam Type : Wide Fixed

Lens Cover : None

Driver Type : Meanwell

Connection Options : Direct Wire

Power Delivery Options : External Driver to Line Voltage

Mounting Options : Specific brackets for application, High Bay, Shoebox, Wall Pack, Cobra Head, Canopy, All Purpose.

Min. Ambient Temp (°F)or(°C) : Minus 20 degrees Celsius

Min. Starting Temperature (°F)or(°C) : Minus 20 degrees Celsius

Maximum Ambient temp (°F)or(°C) : 45 degrees Celsius

Dimming Capability : Yes

Min Dimming Level : 0.1

L70 Life (Hours) : 50000

Warranty : 5 Years

Product Length : 14.7

Product Width : 14.7

Product Height : 1.7

IP Rating : Driver IP 65 / Module IP 40

Construction Material : Die-Cast Aluminum

Dimmable : Yes / Option

Certification: UL Listed, DLC, RoHs, FCC, CE,

