



MODEL# LEDG-RTSN-40-5000K

SPECIFICATIONS

Input Voltage : AC100-277V (347V/480V available)
Input Wattage : 40 watts
Power Factor : 0.9
Operating Frequency : 50/60Hz
LED Count : 14
Led Type : High Power CREE XTE,1-5W
Delivered Lumens (Lm) : 4100
Efficacy Lm/Watt : 102.5
Color Rendering Index (CRI) : >80
Color Temperature : 5000
Equivalent Wattage : 250
Beam Angle Degrees : 120 Degrees
Beam Type : Wide Fixed
Lens Cover : None
Driver Type : Meanwell
Connection Options : Direct Wire
Power Delivery Options : External Driver to Line Voltage
Mounting Options : Specific brackets for application, High Bay, Shoebox, Wall Pack, Cobra Head, Canopy, All Purpose.
Min. Ambient Temp (°F)or(°C) : Minus 20 degrees Celsius
Min. Starting Temperature (°F)or(°C) : Minus 20 degrees Celsius
Maximum Ambient temp (°F)or(°C) : 45 degrees Celsius
Dimming Capability : Yes
Min Dimming Level : 0.1
L70 Life (Hours) : 50000
Warranty : 5 Years
Product Length : 14.7
Product Width : 14.7
Product Height : 1.7
IP Rating : Driver IP 65 / Module IP 40
Construction Material : Die-Cast Aluminum
Dimmable : Yes / Option
Certification: UL Listed, DLC, RoHs, FCC, CE,

