



MODEL# LEDG-RTSN-60-5000K

## SPECIFICATIONS

**Input Voltage** : AC100-277V (347V/480V available)

**Input Wattage** : 60 watts

**Power Factor** : 0.9

**Operating Frequency** : 50/60Hz

**LED Count** : 72

**Led Type** : Phillips 3030 1.5 Watt

**Delivered Lumens (Lm)** : 6000-8100

**Efficacy Lm/Watt** : 110.8

**Color Rendering Index (CRI)** : >80

**Color Temperature** : 5000

**Equivalent Wattage** : 450 watt incandescent/150 watt CFL

**Beam Angle Degrees** : 120 Degrees

**Beam Type** : Wide Fixed

**Lens Cover** : None

**Driver Type** : Meanwell

**Connection Options** : Direct Wire

**Power Delivery Options** : External Driver to Line Voltage

**Mounting Options** : Specific brackets for application, High Bay, Shoebox, Wall Pack, Cobra Head, Canopy, All Purpose.

**Min. Ambient Temp (°F)or(°C)** : Minus 20 degrees Celsius

**Min. Starting Temperature (°F)or(°C)** : Minus 20 degrees Celsius

**Maximum Ambient temp (°F)or(°C)** : 45 degrees Celsius

**Dimming Capability** : Yes

**Min Dimming Level** : 0.1

**L70 Life (Hours)** : 50000

**Warranty** : 5 Years

**Product Length** : 5.19

**Product Width** : 5.19

**Product Height** : 5.11

**IP Rating** : 40

**Construction Material** : Aluminum

**Dimmable** : Yes / Option

**Certification**: UL Listed, DLC, RoHs, FCC, CE,

