



MODEL# LEDG-RTSN-65-4500K

## SPECIFICATIONS

**Input Voltage** : AC100-277V (347V/480V available)  
**Input Wattage** : 65 watts  
**Power Factor** : 0.9  
**Operating Frequency** : 50/60Hz  
**LED Count** : 72  
**Led Type** : Phillips 3030 1.5 Watt SMD  
**Delivered Lumens (Lm)** : 6817  
**Efficacy Lm/Watt** : 104.8769230769231  
**Color Rendering Index (CRI)** : >80  
**Color Temperature** : 4500  
**Equivalent Wattage** : 400  
**Beam Angle Degrees** : 120 Degrees  
**Beam Type** : Wide Fixed  
**Lens Cover** : None  
**Driver Type** : Meanwell  
**Connection Options** : Direct Wire  
**Power Delivery Options** : External Driver to Line Voltage  
**Mounting Options** : Specific brackets for application, High Bay, Shoebox, Wall Pack, Cobra Head, Canopy, All Purpose.  
**Min. Ambient Temp (°F)or(°C)** : Minus 20 degrees Celsius  
**Min. Starting Temperature (°F)or(°C)** : Minus 20 degrees Celsius  
**Maximum Ambient temp (°F)or(°C)** : 45 degrees Celsius  
**Dimming Capability** : Yes  
**Min Dimming Level** : 0.1  
**L70 Life (Hours)** : 50000  
**Warranty** : 5 Years  
**Product Length** : 14.7  
**Product Width** : 14.7  
**Product Height** : 1.7  
**IP Rating** : Driver IP 65 / Module IP 40  
**Construction Material** : Die-Cast Aluminum  
**Dimmable** : Yes / Option  
**Certification**: UL Listed, DLC, RoHs, FCC, CE,

