



MODEL# LEDG-RTSN-480-5700K

SPECIFICATIONS

Input Voltage : AC100-277V (347V/480V available)
Input Wattage : 480 watts
Power Factor : 0.9
Operating Frequency : 50/60Hz
LED Count : 560
Led Type : Phillips 3030 1.5 Watt
Delivered Lumens (Lm) : 48000-62000
Efficacy Lm/Watt : 114.58333333333333
Color Rendering Index (CRI) : >80
Color Temperature : 5700K
Equivalent Wattage : 3500 watt incandescent/1000 watt CFL
Beam Angle Degrees : 120 Degrees
Beam Type : Wide Fixed
Lens Cover : None
Driver Type : Meanwell
Connection Options : Direct Wire
Power Delivery Options : External Driver to Line Voltage
Mounting Options : Specific brackets for application, High Bay, Shoebox, Wall Pack, Cobra Head, Canopy, All Purpose.
Min. Ambient Temp (°F)or(°C) : Minus 20 degrees Celsius
Min. Starting Temperature (°F)or(°C) : Minus 20 degrees Celsius
Maximum Ambient temp (°F)or(°C) : 45 degrees Celsius
Dimming Capability : Yes
Min Dimming Level : 0.1
L70 Life (Hours) : 50000
Warranty : 5 Years
Product Length : 14.96-17.51
Product Width : 10.23
Product Height : 5.11-6.29
IP Rating : 40
Construction Material : Aluminum
Dimmable : Yes / Option
Certification: UL Listed, DLC, RoHs, FCC, CE,

