



MODEL# LEDG-RTSN-35

## SPECIFICATIONS

**Input Voltage** : AC100-277V (347V/480V available)  
**Input Wattage** : 35 watts  
**Power Factor** : 0.9  
**Operating Frequency** : 50/60Hz  
**LED Count** : 14  
**Led Type** : CREE XTE, 1-5W  
**Delivered Lumens (Lm)** : 3300-3900  
**Efficacy Lm/Watt** : 104.6  
**Color Rendering Index (CRI)** : >70  
**Color Temperature** : 4000K, 4500K, 5000K, 5700K  
**Equivalent Wattage** : 100 HID, 250 watt incandescent/70 watt CFL  
**Beam Angle Degrees** : 120  
**Beam Type** : Wide Fixed  
**Lens Cover** : None  
**Driver Type** : HLG-40H-24A ( Mean Well Driver )  
**Connection Options** : Direct Wire  
**Power Delivery Options** : External Driver to Line Voltage  
**Mounting Options** : Patented Multi-Purpose Bracket  
**Min. Ambient Temp (°F)or(°C)** : Minus 20 degrees Celsius  
**Min. Starting Temperature (°F)or(°C)** : Minus 20 degrees Celsius  
**Maximum Ambient temp (°F)or(°C)** : 45 degrees Celsius  
**Dimming Capability** : Yes  
**Min Dimming Level** : 0.1  
**L70 Life (Hours)** : 50000  
**Warranty** : 5 Years  
**Product Length** : 14.7  
**Product Width** : 14.7  
**Product Height** : 1.7  
**IP Rating** : Driver IP 65 / Module IP 40  
**Construction Material** : Die-Cast Aluminum  
**Dimmable** : Yes / Option  
**Certification**: UL Listed, DLC, RoHs, FCC, CE, PSE,

## HIGHBAY BRACKET



## UNIVERSAL BRACKET

